



K-HS5



VAL0122957 / SKC9826780

HEADSET CABLE DESCRIPTION



1 SPECIFICATION

Length	5 m
Connector	Mounted: 3.5mm phono type Enclosed: 6.35mm Panel phono plug (mounted and soldered at installation)
Cable type	4-wire twisted, shielded, 0.25mm ²
Cable sheath	PVC
Temp. range	-10 to +75°C

2 CONNECTION DIAGRAM



3 MOUNTING DESCRIPTION

Eng

Cut the cable to the appropriate length. Solder the cable to the contact according to the figure above: c1=white, c2=brown, c3=green. Cut the shield.

Sve

Klipp kabeln till önskad längd och löd kabel till kontakten enligt figur ovan: c1 = vit, c2 = brun, c = grön. Kapa skåmen vilken inte skall anslutas.

Ger

Das Kabel auf die gewünschte länge kurzen und in den Kontakt wie oben abgebildet einlöten: c1=weiss, c2=braun, c3=grün. Abschirmung entsprechend kürzen.

Fra

Couper le câble à la longueur désirée. Souder le câble au contact selon la figure ci-dessus: c1=blanc, c2=brun, c3=vert. Coupez le blindage.

Fin

Katkaise kaapeli pihdeillä sopivan pituiseksi. Juota kaapeli alustan liittimeen yllä olevan kuvan mukaan: c1=valkea, c2=ruskea, c3=vihreä. Katkaise suojavaippa.

4 CONTACT

Sales, development, production and service:

Dametric AB

Jägerhorns Väg 19, SE 141 75 Kungens Kurva, Sweden
 Phone: +46-8 556 477 00 Telefax: +46-8 556 477 29
 E-Mail: service@dametric.se Website: www.dametric.se

dametric 

Valmet 